

WHAT IS CLAIMED IS:

1. A paging control method of a communication system
that selectively provides one of communication
5 services implemented by integrating a plurality of
communication systems, the paging control method
comprising:

a first step of transmitting a paging signal from
each of the plurality of communication systems to a
10 terminal; and

a second step of receiving the plurality of
paging signals by said terminal, and of selecting a
desired communication system for use by said terminal
from said plurality of communication systems in
15 accordance with information contained in the plurality
of paging signal received.

2. The paging control method as claimed in claim 1,
further comprising a third step of transmitting a
20 connection request signal from said terminal to said
desired communication system selected at the second
step.

3. A paging control method of a communication system
25 that selectively provides one of communication
services implemented by integrating a plurality of
communication systems, and includes a paging agent for

managing paging signals, the paging control method comprising:

a first step of transmitting previously a request for a communication system a terminal wishes to use,
5 and terminal location information of the terminal from the terminal to the paging agent, and of registering the received request and the terminal location information in the paging agent;

a second step of selecting an optimum
10 communication system from among the plurality of communication systems by said paging agent in accordance with the registered request and the terminal location information in said paging agent;
and

15 a third step of transmitting the paging signal from said optimum communication system to said terminal.

4. The paging control method as claimed in claim 3,
20 further comprising a fourth step of transmitting a connection request signal from said terminal to said optimum communication system.

5. A paging control method of a communication system
25 that selectively provides one of communication services implemented by integrating a plurality of communication systems, and includes a paging agent for

managing paging signals, said paging control method comprising:

a first step of transmitting previously a request for a communication system a terminal wishes to use,
5 and terminal location information of the terminal from the terminal to the paging agent, and of registering the received request and the terminal location information in the paging agent;

a second step of selecting an optimum
10 communication system from among the plurality of communication systems by said paging agent in accordance with the registered terminal location information in said paging agent; and

a third step of transmitting a paging signal
15 including a name of said communication system selected at the second step from a given communication system predetermined from among said plurality of communication systems to carry out transmission to said terminal.

20
6. The paging control method as claimed in claim 5, further comprising a fourth step of transmitting a connection request signal from said terminal to said given communication system, and of waiting for an
25 information signal from said optimum communication system contained in said paging signal.

09003913.110601

7. The paging control method as claimed in any one of claims 1, 3 and 5, wherein the second step uses one of a communication cost, a transmission rate, a transmission quality and a combination of at least two of them as a selection index of said optimum communication system.

8. A paging control system of a communication system that selectively provides one of communication services implemented by integrating a plurality of communication systems, the paging control system comprising:

communication control means for causing each of the plurality of communication systems to transmit a paging signal via an external network; and

a terminal for receiving the plurality of paging signals, and for selecting a desired communication system for use from said plurality of communication systems in accordance with information contained in the plurality of paging signal received.

9. The paging control system as claimed in claim 8, wherein said terminal transmits a connection request signal to said desired communication system selected.

10. A paging control system of a communication system that selectively provides one of communication

services implemented by integrating a plurality of communication systems, and includes a paging agent for managing paging signals, the paging control system comprising:

5 a terminal for transmitting previously a request for a communication system a terminal wishes to use, and terminal location information of the terminal from the terminal to the paging agent;

10 registering means for registering the received request and the terminal location information in said paging agent;

15 selecting means in said paging agent for selecting an optimum communication system from among said plurality of communication systems in accordance with the registered request and the terminal location information in said registering means; and

20 communication control means for causing said optimum communication system selected by said selecting means to transmit the paging signal to said terminal.

11. The paging control system as claimed in claim 10, wherein said terminal transmits a connection request signal to said optimum communication system.

25 12. A paging control system of a communication system that selectively provides one of communication

09993918.110601

services implemented by integrating a plurality of communication systems, and includes a paging agent for managing paging signals, the paging control system comprising:

5 a terminal for transmitting previously request for a communication system a terminal wishes to use, and terminal location information of the terminal to the paging agent;

 storing means in said paging agent for
10 registering the received request and the terminal location information;

 selecting means in said paging agent for
 selecting an optimum communication system from among
 the plurality of communication systems in accordance
15 with the registered request and the terminal location information in said storing means; and

 communication control means for transmitting a
 paging signal including a name of said optimum
 communication system selected by said selecting means
20 from a given communication system predetermined from
 among said plurality of communication systems to said
 terminal.

13. The paging control system as claimed in claim 12,
25 wherein said terminal transmits a connection request signal to said given communication system, and waits for an information signal from said optimum

communication system contained in said paging signal.

14. The paging control system as claimed in any one of claims 8, 10 and 12, wherein said selecting means
5 uses one of a communication cost, a transmission rate, a transmission quality and a combination of at least two of them as a selection index of said optimum communication system.

10 15. The paging control system as claimed in any one of claims 8, 10 and 12, wherein said selecting means carries out the selection of said optimum communication system in response to a query about the optimum communication system from said communication
15 control means.

16. A recording medium which records a paging control program in a communication system that selectively provides one of communication services implemented by
20 integrating a plurality of communication systems, and includes a paging agent for managing paging signals, said paging control program, which is used by a computer for controlling said paging agent, causing said computer to:

25 receive from a terminal a request for a communication system said terminal wishes to use, and terminal location information of said terminal;

to register the received request and the terminal location information:

to select an optimum communication system from among the plurality of communication systems in accordance with the registered request and the terminal location information; and

to cause said optimum communication system
selected to transmit the paging signal to said
terminal.

17. A recording medium which records a paging control program in a communication system that selectively provides one of communication services implemented by integrating a plurality of communication systems, and includes a paging agent for managing paging signals, said paging control program, which is used by a computer for controlling said paging agent, causing said computer to:

receive from a terminal a request for a communication system said terminal wishes to use, and terminal location information of said terminal:

register the received request and the terminal location information:

select an optimum communication system from among said plurality of communication systems in accordance with the registered request and the terminal location information; and

cause a given communication system, which is
predetermined from among said plurality of
communication systems communication control means for
carrying out transmission to said terminal, to
5 transmit to said terminal a paging signal including a
name of said optimum communication system selected.

09993918.110601